

Safety Data Sheet

Section 1 - Identification

Product Name	Glassline GA48 Aegean → FUS GL48 Glassline Chalk CH48 Aegean → NO item#
Common Names	Glassline Paint
Company	Clay Art Center Inc 2636 Pioneer Way East Tacoma Wa 98404
Emergency Number	911
Product Use	Glass fusing
Restrictions on Use	None applicable

Section 2 - Hazardous Identification

Contains Crystalline Silica > 1% Respirable

**GHS label elements /
Hazard pictograms**



OSHA / HCS status

In the liquid form this material is not considered hazardous.
If exposed to airborne dust or mist this material is considered hazardous
by OSHA Hazard Communication Standard (29 CFR 1910. 1200)

**Classification of the
substance or mixture**

OSHA - Carcinogenicity (Inhalation) - Category 1A
Specific organ toxicity (Repeated Exposure) (Respiratory tract through
inhalation) - Category 1

Signal Word

Danger

Hazard Statement

(H350) Cancer Hazard. Contains quartz (crystalline silica) which may cause cancer. Risk of cancer depends upon duration and level of exposure to the dust
Not an acute hazard.
(H332) Prolonged inhalation of dust may cause lung injury. Inhalation of high concentrations of dust may cause mechanical irritation and discomfort of the respiratory tract. Repeated exposure may have chronic effects.
Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage.
(H316 + H320 + H335) Can cause skin, respiratory, and eye irritation.
(P261) Avoid breathing dust
(P280) Wear protective gloves, eye, and respiratory protection.

**Precautionary
Statements**

Substances / Mixtures

Mixture - A trade secret claim is made for this item

Component	CAS #	Approx % by Wt.
Crystalline Silica (quartz)	14808-60-7	20
Fluorides , as F	7789-75-5	5
Cobalt or Cobalt Compounds	7440-48-4	1
Chrome Oxide	1313-13-2	1
Zirconium or Zirconium Compounds	7440-67-7	3

Eye Contact	If eye contact occurs, rinse immediately with plenty of water. If irritation persists, seek medical attention.
Skin Contact	If irritation occurs, wash thoroughly with water. If it persists, seek medical attention.
Inhalation	Move victim to fresh air in well ventilated area. If coughing or irritation persist, seek medical attention.
Ingestion	Do not induce vomiting. Rinse mouth thoroughly with water. Give a few small glasses of water or milk to drink. Get medical attention if any discomfort continues.

Symptoms and Effects, both Acute and Delayed

Eye Contact	Prolonged contact with large amounts of dust may cause mechanical irritation.
Skin Contact	Prolonged contact with large amounts of dust may cause mechanical irritation.
Inhalation	Inhalation of high concentrations of dry dust may cause mechanical irritation and discomfort. Long term exposure may cause chronic effects (see section 11)
Ingestion	Large quantities ingested may cause gastrointestinal irritation.
Chronic Symptoms	Repeated or prolonged exposure to respirable crystalline silica dust may cause lung damage in the form of silicosis. Symptoms will include shortness of breath, fever, fatigue, loss of appetite, chest pain, dry non-productive cough.

Section 5 - Fire Fighting Measures

General Fire Hazards	Glassline mixture is not flammable and does not support fire. The plastic bottle containing the mixture are flammable.
Extinguishing Media	Use appropriate extinguishing media for surrounding fire.
Chemical Hazards from Fire	Glassline mixture does not contain hazardous decomposition products.
Protective Actions and Equipment for Fire-fighters	Glassline mixture and packaging can become slippery when wet. Fire-Fighters should wear appropriate protective equipment.

Section 6 - Accidental Release Measures

Clean - up Methods	Sponge or mop spill using plenty of water.
Personal Precautions and Personal Protection Equipment	Wear appropriate protective equipment and clothing during clean-up. When dry sweeping use NIOSH approved respirators when dust levels exceed exposure limits.
Enviromental Precautions	None
Emergency Procedures and Methods of Containment	There is no emergency procedures required for this mixture. Place dry powder in a sealed container for proper disposal.

Section 7 - Handling and Storage

Precations for Safe Handling	Use proper lifting techniques to avoid injury.
Recommendations on the Conditions for Safe Storage	Store in a clean dry location.

Airborne Exposure Limits and Personal Protection

Airborne Exposure Limits

Hazardous Ingredient	Wt. % Aprox.	CAS#	OSHA PEL* / ACGIH TLV
Crystalline Silica (quartz)	20	14808-60-7	0.1 mg/m3 / 0.025mg/m3 respirable
Fluorides , as F	5	7789-75-5	2.5 / 2.5
Chrome Oxide	1	1313-13-2	0.5 mg/m3 / 0.5 mg/m3
Cobalt or Cobalt Compounds	1	7440-48-4	0.1 / 0.02
Zirconium or Zirconium Compounds	3	7440-67-7	5 / 5

Engineering Measures Provide sufficient ventilation for operations causing dust formation.
Observe occupational exposure limits and minimize the risk of exposure.

Personal Protective Equipment (PPE)

Respiratory If engineering controls do not maintain airborne concentrations below recommended exposure limits an approved respirator must be worn.
Use a NIOSH/MSHA approved air purifying respirator as needed to control exposure.

Eyes Wear approved safety goggles.

Skin and Body It is a good industrial hygiene practice to minimize skin contact. For prolonged contact use suitable protective gloves.

Appearance	Dry Powder	Evaporation Rate	Not Applicable
Color	Aqua	Solubility in Water at 100c	None
Physical State	Liquid	Viscosity	Not Applicable
ph	6-8	Flashpoint	Not Applicable
Odor	low to none	Boiling Point	Not Applicable
Odor Threshold	Not Applicable	Flammability	Not Applicable
Melting Point	Not Applicable	Vapor Pressure(mm HG)	Not Applicable
Freezing Point	Not Applicable	Vapor Density	Not Applicable
Relative Density /		Particiclan coefficient	Not Applicable
Specific Gravity	1.76 (H2O=1)	Auto Ignition Temp.	Not Applicable

Section 10: Stability and Reactivity

Reactivity	No dangerous reactions are known under normal conditions of use.
Chemical Stability	Material is stable under normal conditions.
Possibility of Hazardous Reactions	Hazardous polymerization does not occur.
Conditions to Avoid	Airborne dust
Incompatible Materials	None
Hazardous Decomposition Products	None

Section 11: Toxicological Information

Primary Route of Exposure	Skin, Eye Contact, Inhalation and Ingestion.
Specific Organ Toxicity Single Exposure	Target organs include Skin and respiratory system
Specific Organ Toxicity Repeated Exposure	Cause damage to eyes, skin and respiratory system through prolonged or repeated exposure.
Acute Short Term Exposure Effects	May cause eye irritation, skin irritation and respiratory tract irritation Inhalation of high concentrations of dry powder may cause mechanical irritation and discomfort. Long term exposure may cause chronic effects.
Chronic Long Term Exposure Effects	Silica has been classified by OSHA as a human lung carcinogen. Repeated or prolonged exposure of respirable crystalline silica dust may cause lung damage in the form of silicosis. Effects of silicosis include bronchitis/chronic obstructive pulmonary disorder, increased susceptibility to tuberculosis, scleroderma (a disease affecting skin, blood vessels, joints and skeletal muscles),and possible renal disease. Acute silicosis can be fatal.
Related Symptoms	Symptoms will include shortness of breath, fever, fatigue, loss of appetite, chest pain, dry non-productive cough.
Medical Conditions Aggravated by Exposure	Individuals with pre-existing allergies, eye disorders, skin disorders, respiratory disorders may have increased susceptibility to the effects of exposure.

Ecotoxicity	None known
Biochemical Oxygen Demand (BODS)	None Known
Chemical Oxygen Demand (COD)	None Known
Products of Biodegradation	None Known
Toxicity of the Products of Biodegradation	None Known
Bioaccumulation Potential	None Known
Potential to Migrate from Soil to Groundwater	None Known
Other Adverse Effects	None Known

Section 9: Disposal Considerations (Environmental Protection)

Personal Protection	Refer to section 8 for proper PPE when disposing of waste material.
Appropriate Disposal Containers	Standard waste disposal containers - no special requirements.
Appropriate Disposal Methods	Disposal of this product should comply with the requirements of environmental protection and waste disposal legislation and any regional or local authority requirements.
Physical and Chemical Properties that May Affect Disposal	Dry dust should be placed in a sealed container or in a manner that reduces or eliminates the release of the product.
Spillage Disposal	No precautions
Special Precautions for Landfills or Incineration Activities	There are no special precautions for disposal in a landfill. This product is non-combustible and is not suitable for incineration.

Section 10: Transportation Information (Transportation)

Regulatory Information	UN Number	UN Proper Shipping Name	Transport Hazard Class	Packing Group Number	Bulk Transport Guidance	Special Precautions
DOT Classification	Not Regulated	-	-	-	-	-
TDG Classification	Not Regulated	-	-	-	-	-
ADR/RID Class	Not Regulated	-	-	-	-	-
IMDG Class	Not Regulated	-	-	-	-	-
IATA-DGR Class	Not Regulated	-	-	-	-	-

Section 11: Regulatory Information (Regulatory Information)

TSCA - Toxic Substance	Quartz and other chemicals are listed in the TSCA Substance Inventory.
California Prop. 65 Warning	This product contains a chemical known to the State Of California to cause cancer. (Prop 65 - California Health and Safety Code Section 2549 Et Seq)
SARA / Title III (Emergency Planning and Community Right to Know Act	This mixture contains no substance at or above the reporting threshold under section 313, based on available data

Section 12: Definitions (Definitions)

Definitions

ACGIH	American Conference of Governmental Industrial Hygienist
CAS	Chemical Abstract Service
CAL-OSHA	California Occupational Safety and Health Administration
IARC	International Agency for Research on Cancer
OSHA	Occupational Safety and Health Administration
MSHA	Mine Safety and Health Administration
NIOSH	National Institute of Occupational Safety and Health
NTP	National Toxicology Program
HCS	Hazardous Communication Standard
OSHA PEL	OSHA Permissible Exposure Limit
STEL	Short Term Exposure Limit
TLV	Threshold Limit Value
TWA	Time Weighted Average

Three types of TLVS for chemical substances as defined by the ACGIH are:

TLV-TWA	Time weighted average - average exposure on the basis of an 8 h/day, 40h/week work schedule.
TLV - STEL	Short - term exposure limit - spot exposure for a duration of 15 minutes, that can not be repeated more than 4 times per day, with at least 60 minutes between exposure periods.
TLV-C	Ceiling limit - absolute exposure limit that should not be exceeded at any time.

This SDS is in compliance with The Globally Harmonized System of Classification and Labeling of Chemicals (GHS) and is subject to revision at any time without notice. Its current revision date is : 11/25/2016

Information presented herein has been compiled from sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so. Nothing herein is to be construed as recommending any practice or any product in violation of any patent or in violation of any law or regulation. It is the user's responsibility to determine for himself the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary. We make no warranty as to the results to be obtained in using any material and, since conditions of use are not under our control, we must necessarily disclaim all liabilities and respect to the use of any material supplied by us.

