

# SAFETY DATA SHEET

## Maker's Mudd

Prepared by: **Little Glass Art**

9780 E Girard Ave, Denver, CO 80231

Email: [hello@littleglassart.co](mailto:hello@littleglassart.co) | Phone: 719-445-6551

---

### SECTION 1 – Identification

**Product Name:** Maker's Mudd

**Recommended Use:** To clean and weatherproof stained glass windows

**Manufacturer:** Little Glass Art

---

### SECTION 2 – Hazard Identification

**Signal Word:** WARNING

**Hazard Statements:** - Flammable liquid and vapor

- Causes skin irritation
- Harmful if inhaled
- May cause allergic skin reaction
- Toxic to aquatic life with long-lasting effects

**Precautionary Statements:** - Keep away from heat, sparks, open flame, and hot surfaces

- Avoid breathing vapors
  - Wear protective gloves
  - Use only outdoors or in well-ventilated areas
  - Dispose of contents/container in accordance with local regulations
-

### SECTION 3 – Composition / Information on Ingredients

| Ingredient                        | CAS Number | Approx. % | Classification                               |
|-----------------------------------|------------|-----------|----------------------------------------------|
| Calcium Carbonate (Whiting)       | 471-34-1   | 60–70%    | Not hazardous                                |
| Turpentine                        | 8006-64-2  | 15–20%    | Flammable, irritant, allergen, aquatic toxin |
| Boiled Linseed Oil                | 8001-26-1  | 10–15%    | Combustible, skin irritant                   |
| Black Chalk (Carbon/Clay mixture) | variable   | <1%       | Not hazardous                                |

---

### SECTION 4 – First Aid Measures

- **Skin:** Wash thoroughly with soap and water. Remove contaminated clothing.
- **Eyes:** Rinse cautiously with water for several minutes.
- **Inhalation:** Move to fresh air.
- **Ingestion:** Rinse mouth. Do not induce vomiting. Seek medical attention if symptoms persist.

---

### SECTION 5 – Firefighting Measures

- **Suitable Extinguishing Media:** Dry chemical, foam, CO<sub>2</sub>
- **Flash Point:** ~35°C (due to turpentine)
- **Fire Hazards:** Combustible liquid. Vapors may form explosive mixtures with air.

---

### SECTION 6 – Accidental Release Measures

Avoid ignition sources. Absorb with inert material and place in chemical waste container.

---

## SECTION 7 – Handling and Storage

Keep away from heat, sparks, and open flame. Store in a cool, dry, well-ventilated area.

---

## SECTION 8 – Exposure Controls / Personal Protection

Use with adequate ventilation. Wear gloves and eye protection. Avoid inhalation of vapors.

---

## SECTION 9 – Physical and Chemical Properties

- **Appearance:** Creamy paste
  - **Odor:** Pine oil
  - **pH:** Neutral
  - **Solubility:** Insoluble in water
  - **Base:** Oil and mineral filler
- 

## SECTION 10 – Stability and Reactivity

Stable under normal conditions. Avoid strong oxidizers and heat sources.

---

## SECTION 11 – Toxicological Information

Turpentine: May cause respiratory irritation and allergic skin reaction.  
Linseed oil: Mild irritant.

---

## SECTION 12 – Ecological Information

Turpentine is toxic to aquatic life. Avoid release to the environment.

---

## SECTION 13 – Disposal Considerations

Dispose of in accordance with local, regional, and national regulations. Do not pour into drains.

---

## SECTION 14 – Transport Information

- **UN Number:** 1299 (Turpentine)
  - **Class:** 3 (Flammable liquid)
  - **Packing Group:** III
- 

## SECTION 15 – Regulatory Information

OSHA Hazard Communication Standard (29 CFR 1910.1200) compliant.

---

## SECTION 16 – Other Information

**Revision Date:** November 2025

**Prepared by:** Little Glass Art

**Legal disclaimer:** The information provided in this Safety Data Sheet is correct to the best of our knowledge, information, and belief at the date of its publication. The information provided is intended solely as guidance for safe handling, use, processing, storage, transportation, disposal, and release, and should not be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process unless specified in the text.